

# tesa® 4437

**UV Paper Mask** 

# PRODUCT INFORMATION

## **Product Description**

tesa® 4437 UV Paper Mask is applicable with all kind of paints and its conformability allows a masking of slight curves as well as a masking in straight lines. The combination of the conformable backing material and the special adhesive formulation allows easy residue free removability up to 6 weeks after outdoor application. This enables multiple working processes in only one covering process.

## **Main Application**

This tape is suited for almost all outdoor paint works. It is suitable for outdoor applications on a variety of common surfaces and especially when a clear and sharp paint edge is needed.

#### **Technical Data**

- Backing material
- Type of adhesive
- Total thickness
- Adhesion to steel
- slightly-creped paper
- acrylic 150 µm

3.4 N/cm

Tensile strength

Elongation at break

- 14 %
- 45 N/cm
- UV-resistance 6 Weeks

## **Properties**

- Paint anchorage
- Conformability

- Sharp colour Edge

- Hand tearability

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

## **Additional Info**

The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Therefore we strongly recommend a test application before.

Page 1 of 1 / As of 10/30/09

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707

tesa tape inc.

# tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle Singapore 629621

Phone: +65 (68) 612 026 Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.